

HARKEN®

INSTALLATION SHEET

437 16mm Flip-Flop Block


1251 East Wisconsin Avenue • Pewaukee, WI 53072 U.S.A.

Telephone: (262) 691-3320 • Fax: (262) 691-3008

Web: <http://www.harken.com> • E-mail: harken@harken.com

Fastener Size	Drill Ø	Tap
#8 Tapped hole	1/8"	#8
#8 Through-bolted	11/64"	—
5/32" Rivet	5/32"	—
M4 Tapped hole	1/8"	M5
M4 Through-bolted	11/64"	—

See drawing at right
for correct carrier
orientation and
clevis pin installation



Maintenance

Harken equipment requires minimal maintenance, but some is required to give the best service and to comply with Harken's limited warranty.

It is important to keep equipment clean by frequently flushing with fresh water. In corrosive atmospheres, stainless parts may show discoloration around holes, rivets and screws. This is not serious and may be removed with a fine abrasive.

With the exception of winches, do not use grease unless specifically recommended in the instruction sheets.

Important: Exposure to some teak cleaners and other caustic solutions can result in discoloration of part and is not covered under the Harken warranty.

Warranty

See the Harken catalog or www.harken.com for additional maintenance and warranty information.

Printed in USA. 4852/9-08